



Delta BFR



Stems grinder

Delta BFR solves the problem of stems which pile up when grapes are picked off the bunch. When it is placed after the destemmer, this grinder allows to reduce by 80% the volume of stems (space is saved) and thus to limit handling (time is saved).



Juice collection tub



Frame manually adjustable from height (optional)

Benefits:

- Stems volume is reduced by 80%.
- Compact.
- Designed for destemmers E2, Evolution 2, Oscillys 50, 100 and 200 for a maximum flowrate of 12 T/H of treated whole grapes depending on grape varieties.
- Easy to handle thanks to 2 swiveling wheels and ergonomic arm.
- The juices produced when shredding the stems are collected in a bin - outlet DIN 40.

Technical characteristics:

- 1 Rotor equipped with 55 moving knives and 23 dead knives.
- 1 integrated belt conveyor, width 500 mm, designed to unload into a container 700 mm high and up to 1000 mm with the extension frame.
- Belt cover in stainless steel for higher resistance and safety.
- Construction in stainless steel.
- Weight: 160 kg.
- Power 1.5 kW.
- Frame manually adjustable from height +135 mm to + 335 mm (optional).

Use of shredded stems.

- Distillation depending on the regulation in force.
- Spreading depending on the regulation in force.
- Recycling in biomass (Pellet).

Environment:

- Range of troughs adapted to destemmers E2 / Evolution 2 and Oscillys 50/100/200
(**Beware :** The Delta BFR must be tightly fastened to the destemmer and the trough must not allow the access to the knives).



Adaptation Delta BFR under a Delta Oscillys 50



Adaptation Delta BFR under a Delta Evolution 2

Distributed by:

Bucher Vaslin

Rue Gaston Bernier - BP 70028
F - 49290 Chalonnes sur Loire
Tél. +33 (0)2 41 74 50 50
Fax +33 (0)2 41 74 50 51
E-mail : commercial@buchervaslin.com

www.buchervaslin.com
Your success is our priority